





















PRODUCT CATALOGUE





INTRODUCTION

Established in the year 2019, We UDK ELECTRICAL INDUSTRIES PVT LTD." are engaged in Manufacturing of Indoor, Outdoor & Industrial Lights.

We design and produce innovative LED products of excellent quality, competitive price supported by a nationwide network of sales and services.

We are highly appraised by our clients and the markets for our credible quality after-service. Therefore, our products are widely applauded for having various features like excellent lighting, power saving, durability, minimum maintenance, low energy consumption and High corrosion resistance.

Owing to having features like these, our products are used in various Offices, Households, Garden, Industries & etc.

UDK ELECTRICALINDUSTRIES PVT LTD. is a leading, fullspectrum provider of professional and Architectural lighting solutions. Built on over a century of expertise in led lights and luminaries, we are your best one -stop service for differentiated product solution provider.





-

M







Slim Conceal Panel Light

WATT	сит оит	OUTER	COLOUR
4W	65mm	85mm	WH/NW/WW
8W	105mm	120mm	WH/NW/WW
15W	155mm	170mm	WH/NW/WW
22W	205mm	220mm	WH/NW/WW
30W	275mm	295mm	WH
40W	575mm	595mm	WH

*40W(2X2) available in Sq Shape

Surface Panel Light						
WATT	OUTER	COLOUR				
8W	110mm	WH/NW/WW				
15W	160mm	WH/NW/WW				
22W	220mm	WH/NW/WW				
30W	295mm	WH				

*30W available in Sq Shape





Rimless Conceal Panel Light					
WATT	CUT OUT	OUTER	COLOUR		
8W	70mm	85mm	WH/NW		
15W	120mm	145mm	WH/NW		
22W	150mm	175mm	WH/NW		

Rimless	Surface	Conceal Panel Light	
WATT	OUTER	COLOUR	
8W	85mm	WH/NW	
15W	145mm	WH/NW	
22W	175mm	WH/NW	





Slim	3in 1 Pan	el Light	
WATT	сит оит	OUTER	COLOUR
8W	105mm	120mm	3in1
15W	155mm	170mm	3in1
22W	205mm	220mm	3in1

* Aluminum body (WH/WW/NW)

Deep	Deep Down Panel Light					
WATT	CUT OUT	OUTER	COLOUR			
12W	110mm	120mm	WH/NW/ 3in1			
18W	145mm	155mm	WH/NW/ 3in1			
24W	165mm	175mm	WH			

* 12W &18W available in WH /BK body

* Aluminum body





2 in 1 C	onceal Pan	el Light		2 in 1 C	olor Surfac	e Panel Light	
WATT	CUT OUT	OUTER	COLOUR	WATT	OUTER	COLOUR	
3+3W	65mm	100mm	WH+BL/PK/PGB	3+3W	100mm	WH+BL/PK/PGB	
6+3W	100mm	145mm	WH+BL/PK/PGB	6+3W	145mm	WH+BL/PK/PGB	
12+4W	150mm	195mm	WH+BL/PK/PGB	12+4W	195mm	WH+BL/PK/PGB	

*3+3W also available in Jelly Design





PC B	acklit Pane	el Light	
WATT	CUT OUT	OUTER	COLOUR
8W	100mm	120mm	WH/NW/WW/3in1
15W	125mm	145mm	WH/NW/WW/3in1
15W	150mm	170mm	WH/NW/WW/3in1
22W	150mm	170mm	WH/NW/WW/3in1

* Body material PC

PC Pa	nel Surface Ring
WATT	OUTER
8W	120mm
15W	145mm
22W	170mm





Frameless Adjustable Light			PC I	Deep Down	Panel Ligh	it	
WATT	CUTOUT	OUTER	COLOUR	WAT	г ситоит	OUTER	COLOUR
10W	50-70mm	90mm	WH/NW/3in1	8W	105mm	120mm	WH/NW/WW/3in1
15W	50-100mm	120mm	WH/NW/3in1	15W	130mm	150mm	WH/NW/WW/3in1
22W	50-150mm	170mm	WH/3in1	22W	155mm	170mm	WH/NW/WW/3in1

*Available in WH/BK body











Spot Light COB						
BODY COLOUR	COLOUR					
WH	WH/WW/BL/PK/RED/GR WW					
BK	WH/WW/BL/PK/RED/GR					
WH						
BK/WOODEN	ww					
	BODY COLOUR WH BK WH					

PC Mo	PC Movable COB Light					
WATT	ситоит	OUTER	COLOUR			
3W	55mm	70mm	WH/NW/WW/BL/PK/RED/ GR/RGB/3in1			
6w	70mm	90mm	WH/WW/BL/PK/GR			
9W	85mm	115mm	WH/WW			





Aluminum Movable COB Light		Delta COB Light					
WATT	ситоит	COLOUR		WATT	ситоит	COLOUR	
4W	55mm	WH/WW/NW		7W	55mm	WH/WW/NW/3in1	
9W	75mm	WH/WW/NW		12W	75mm	WH/WW/NW/3in1	
16W	95mm	WH/WW/NW		18W	85mm	WH/WW/NW	
24W	125mm	WH/WW/NW		**			
30-36W	140mm	WH/WW/NW		° Availab	le in WH/BK bo	ay	







Surface Cylinder COB Light

WATT	ситоит	COLOUR
7W	55mm	WH/WW/NW/3in1
12W	75mm	WH/WW/NW/3in1
18W	85mm	WH/WW/NW

Creta COB Light

ситоит	COLOUR
60mm	WH/WW/NW/3in1
75mm	WH/WW/NW/3in1
85mm	WH/WW/NW
	60mm 75mm

*Reflector available : Rose Gold, Shining Black, Chrome





Surface Cylinder COB Light			
	WATT	COLOUR	
	7W	WH/WW/NW/3in1	
	12W	WH/WW/NW/3in1	
	18W	WH/WW/NW	
*Reflector available : Rose Gold, Shining Black			

Linea COB Light		
MODEL	COLOUR	
1EYE	NW/WW	
2EYE	NW/WW	
3EYE	NW/WW	
5EYE	NW/WW	

*WH color available on order basis





Surface Rimless Cylinder COB Light	
WATT	COLOUR
12W	WH/NW
18W	WH /NW

Pull – Out 360 Light		
WATT	COLOUR	













LED V	Vall Light	
WATT	COLOUR	
3W	WH/WW/NW	
6W	WH/WW/NW	
10W	WH/WW/NW	
20W	WH/WW/NW	
30W	WH/WW/NW	

LED MAGNETIC LIGHTS

.....

LED MAGNETIC LIGHTS









Ultra Slim Surface Mounted Track

ITEM	MATERIAL
1 m/pc	Aluminum
2 m/pc	Aluminum
Track Cover	PC Dust proof

*Input Voltage : DC 48V

Connector for Surface Mounted

ITEM	
Thin straight connector	
Thin 90 [•] connector	
Cover box	

*Use in Surface track

APPLICATION

For straight track connector For90 [•]track connector To cover the input cable





Recessed Mounted Track

ITEM MATERIAL 1m/pc Aluminum 2m/pc Aluminum SIZE 30*27.6mm

30*27.6mm

Spring Iron

* Input Voltage : DC48V







Connector for Recessed Mounted

ITEM

Thick straight connector Thick90°connector Thick 90° connector

* Use in Recessed Track

APPLICATION

Straight track connector 90[®]track connector for same surface 90[®] track connector for wall to ceiling



Power Supply

WAT	
100W	
200W	

MATERIAL Alum + PC + Copper Alum+ PC + Copper



Magnetic Linea Light

WATT	SIZE
6W	L158*W26*H25mm
12W	L273*W26*H25mm
18W	L387*W26*H25mm
24W	L500*W26*H25mm

*CCT: 4000K

LED MAGNETIC LIGHTS







Magnetic Profile Light

WATT	SIZE
12W	L273*W26*H25mm
18W	L387*W26*H25mm
24W	L615*W26*H25mm
* CCT:4000K	

Magnetic Foldable Linea

SIZE L135*W33*H50mm

L250*W33*H50mm

L365*W33*H50mm



*CCT:4000K





Magnetic Hanging Light

WATT	SIZE
12W	Φ 40*300mm

* CCT:4000K



Magnetic Corner Light

WATT	SIZE
12W	165*W137*H25mm
24W	280*W255*H25mm

APPLICATION **Useful for corner track** Useful for90^e track

*CCT : 4000K

WATT

6W 12W

18W

* CCT:4000K



18W

Magnetic Straight Light

SIZE

APPLICATION L387*W26*H25mm Useful for 2 straight track

*CCT: 4000K

WATT





LED PROFILE LIGHT



ò





SMPS & STRIP LED





Ultra Slim SMPS Power Supply

Available in 2A, 3A, 5A, 10A, 12.5A, 16.5A, 25A, 33.3A

* Operating Voltage : 12V

Water proof Power Supply LED Strip

Available in 2A, 3A, 5A, 10A

* Operating Voltage : 12V





LED Strip		
MODEL	WIDTH	COLOUR
2835-120L	5mm	WH/WW/NW
2835-120L	8mm	WH/NW/WW/BL/PK/RED/GR /AMBER/ICE-BLUE
2835-240L	10mm	WH/NW/WW/BL/PK/RED/GR
2835-180L		3in1
5050-120L		3in1/RGB

LED Profile Housing		
SIZE	DEPTH	ТҮРЕ
5mm	5mm/10mm	Conceal / Surface
10mm	6mm/10mm	Conceal / Surface
17mm	6mm/12mm	Conceal/ Surface
25mm	6mm/12mm	Conceal /Surface
35mm	12mm	Conceal
35mm	35mm	Conceal/Surface
50mm	35mm	
	Conceal/Sur	face17mm
	Corner Pro	file

* Standard Length: 2Meter

AVAILABLECOLOUR

WHITE

AMBER

RED

ICE BLUE

WARM WHITE

PINK



LED ROPE LIGHT 8MM |10MM |12MM 5050 LED | 2850 LED WH/WW/BL/RED/GR/PK/AMBER/ ICE-BLUE/6COLORRGB

> WH/WW/BL/RED/GR/PK 16COLORRGB

* Rope cord for each model

available

BLUE

GREEN

RGB

Extended Range





LED Garden Light (IP65)

WATT	COLOUR
3	WH/WW/BL/RED/GR
5	WH/WW/BL/RED/GR/RGB
9	WW/BL/RED/GR
12	WW/RGB



LED Mirror Light			
WATT	COLOUR	TYPE	
6	WH/WW	SLIM/CURVE	

SLIM/CURVE

WH/WW



LED Study Lamp Light		
WATT	COLOUR	
3	WW/WH	

		Lic	111
	_		

12

WATT	COLOUR
5	ww
10	ww





LED Foot Light

MODEL	COLOUR	TYPE
1M	ww	Conceal
2M	ww	Conceal / Surface
4M	ww	Conceal / Surface
6M	ww	Conceal

LED Wall Cylinder Light

WATT	COLOUR
5	ww
10	ww

Extended Range





LED Bulk head Light

WATT	COLOUR
9	WH/WW
18	WH/WW

LED Junction Light

- WATT COLOUR
 - 3 WH/WW/BL/PK/RED/GR/3in1/RGB
 - 4 WH/WW/BL/PK/RED/GR/3in1/RGB



LED Surface COB Light

WATT	COLOUR	BODYCOLOUR
3	ww	BK/WH/WOODEN



LED Striker Light

WATT	COLOUR
	COLOU

3 WH/WW/BL/PK/RED/GR



LED Tube Light				
WATT	COLOUR	LENGTH		
5	WH/WW/BL/PK/RED/GR	1FT		
10	WH/WW/BL/PK/RED/GR	2FT		
20	WH/WW	4FT		

LED Cabinet Light		
SIZE	COLOUR	
1FT	WH/WW/NW	
2FT	WH/WW/NW	
3FT	WH/WW/NW	
4FT	WH/WW/NW	

STREET LIGHT



LED STREET LIGHT



Zredu Cert Fication		
		BIS Approved
		K

LED	LED Street Light (Glass Model)				
WATT	COLOUR	I/PVOLTAGERANGE			
18	3000K-6500K	AC85-300V@50Hz			
24	3000K-6500K	AC85-300V@50Hz			
30	3000K-6500K	AC85-300V@50Hz			
36	3000K-6500K	AC85-300V@50Hz			
50	3000K-6500K	AC85-300V@50Hz			
72	3000K-6500K	AC85-300V@50Hz			
100	3000K-6500K	AC85-300V@50Hz			
150	3000K-6500K	AC85-300V@50Hz			



- Toughened glass cover /PC lens ٠
- ٠ cover Aluminum Die-cast body
- Internal Surge protection Up to 6kV ٠
- External Surge protection 10 KV as per requirement ٠
- IP66 Drivers (isolated) ٠
- >120-140Lumens/watt •
- Higher volt Auto Cut off
- OSRAM / BRIDGELUX / BMTC Or Equivalent As Per Requirement
- Operating Temperature -10° to 50°
- Average Life- 50000 Working Hours
- ٠ Warranty 2 years

Applications















Streets

High Way **Petrol Pump**

Railway Station

Parking

Colonies

Airport

Factory



18	3000K-6500K	AC85-300V@50Hz
24	3000K-6500K	AC85-300V@50Hz
30	3000K-6500K	AC85-300V@50Hz
36	3000K-6500K	AC85-300V@50Hz
50	3000K-6500K	AC85-300V@50Hz

WATT	COLOUR	I/PVUL I AGERANGE
18	3000K-6500K	AC85-300V@50Hz
24	3000K-6500K	AC85-300V@50Hz
30	3000K-6500K	AC85-300V@50Hz
36	3000K-6500K	AC85-300V@50Hz
50	3000K-6500K	AC85-300V@50Hz
72	3000K-6500K	AC85-300V@50Hz
100	3000K-6500K	AC85-300V@50Hz
150	3000K-6500K	AC85-300V@50Hz

LED Street Light (Lens Model) WATT COLOUR I/PVOLTAGERANGE

LED STREET LIGHT





LED Street Light With 5050 High PowerLED

WATT COLOUR I/PVOLTAGERANGE 150 3000K-6500K AC85-300V@50Hz 200 3000K-6500K AC85-300V@50Hz 250 3000K-6500K AC85-300V@50Hz 300 3000K-6500K AC85-300V@50Hz

LED	Street	Light	with	5050	High	Power	LED	Č,	Lens

WATT	COLOUR	I/PVOLTAGERANGE
150	3000K-6500K	AC85-300V@50Hz
200	3000K-6500K	AC85-300V@50Hz
250	3000K-6500K	AC85-300V@50Hz
300	3000K-6500K	AC85-300V@50Hz

Technical Specifications

- Toughened glass cover /Secondary lens for better light distribution
- Aluminum Die cast body
- Internal Surge protection Upto 6kV
- External Surge protection 10KV as per requirement
- IP66 Drivers (isolated)
- >120-140 Lumens/watt
- Higher volt Auto Cut off
- OSRAM / BRIDGELUX / BMTC Or Equivalent As Per Requirement
- Operating Temperature-10°to50°
- Average Life 50000 Working Hours
- Warranty 2 years

Applications









Parking



Airport





High Way

Petrol Pump

Railway Station

Colonies

Factory

SOLAR LIGHT

5

And the set of the set of the set of

1.4

Bun-

11100100

1111



LED SOLAR LIGHT







Solar	Street Light	LED S	olar Street Light	All In One
WATT	COLOUR	WATT	COLOUR	
20	6000K-6500K	20	6000K-6500K	
40	6000K-6500K	40	6000K-6500K	
60	6000K-6500K	60	6000K-6500K	

*Light comes with remote control

Technical Specifications

- Body Material-ABS
- Charging time : 6-8hours
- Lighting duration: 12-15 hours of sustainable lighting
- Battery type : lithium iron hydrochloride battery
- Product configuration: radar + remote control (available on some models)
- Radar sensor : 100% brightness when people come 30% brightness when people leave.
- It can also working no sensor mode with 100% brightness.



Applications















Streets

High Way

Petrol Pump

Railway Station

Parking

Colonies

Airport

Factory



LED FLOOD LIGHT







LED Flood Light Down - Chowk

WATT	COLOUR	I/PVOLTAGERANGE
30	3000K-6500K	AC85-300V@50Hz
50	3000K-6500K	AC85-300V@50Hz
100	3000K-6500K	AC85-300V@50Hz
150	3000K-6500K	AC85-300V@50Hz
200	3000K-6500K	AC85-300V@50Hz
250	3000K-6500K	AC85-300V@50Hz
300	3000K-6500K	AC85-300V@50Hz
350	3000K-6500K	AC85-300V@50Hz
400	3000K-6500K	AC85-300V@50Hz

WATT COLOUR I/PVOLTAGERANGE 30 3000K-6500K AC85-300V@50Hz 50 3000K-6500K AC85-300V@50Hz 100 3000K-6500K AC85-300V@50Hz 150 3000K-6500K AC85-300V@50Hz 200 3000K-6500K AC85-300V@50Hz 250 3000K-6500K AC85-300V@50Hz 300 3000K-6500K AC85-300V@50Hz 350 3000K-6500K AC85-300V@50Hz 400 3000K-6500K AC85-300V@50Hz

LED Lens Flood Light

Technical Specifications

- Aluminum Die cast body ٠
- Internal Surge protection Up to 6kV ٠
- External Surge protection 10KV as per requirement
- ٠ **IP65 Drivers (isolated)**
- >120-140 Lumens/watt ٠
- **Higher volt Auto Cut off**
- OSRAM / BRIDGELUX / BMT C Or Equivalent As Per Requirement
- **Operating Temperature 10°to50°**
- Average Life -50000 Working Hours
- Warranty 2 years

Applications



















Streets

High Way

Petrol Pump

Parking

26

Colonies

Airport

Factory

Railway Station

LED FLOOD LIGHT







LED Flood Light Back - Chowk

WATT	COLOUR	I/PVOLTAGERANGE
30	3000K-6500K	AC85-300V@50Hz
50	3000K-6500K	AC85-300V@50Hz
100	3000K-6500K	AC85-300V@50Hz
150	3000K-6500K	AC85-300V@50Hz
200	3000K-6500K	AC85-300V@50Hz
250	3000K-6500K	AC85-300V@50Hz
300	3000K-6500K	AC85-300V@50Hz
350	3000K-6500K	AC85-300V@50Hz
400	3000K-6500K	AC85-300V@50Hz
500	3000K-6500K	AC85-300V@50Hz
600	3000K-6500K	AC85-300V@50Hz

I Source Course Course

LED Flood Light Premium With High Power LED

WATT	COLOUR	I/PVOLTAGERANGE
100	3000K-6500K	AC85-300V@50Hz
200	3000K-6500K	AC85-300V@50Hz
300	3000K-6500K	AC85-300V@50Hz
400	3000K-6500K	AC85-300V@50Hz
500	3000K-6500K	AC85-300V@50Hz
600	3000K-6500K	AC85-300V@50Hz

Technical Specifications

- Aluminum Die cast body
- Internal Surge protection Up to 6kV
- External Surge protection 10KV as per requirement
- IP65 Drivers (isolated)
- >120-140 Lumens/watt
- Higher volt Auto Cut off
- OSRAM / BRIDGELUX / BMTC Or Equivalent As Per Requirement
- Operating Temperature-10°to50°
- Average Life 50000 Working Hours
- Warranty 2 years

Applications

















Railway Station

Parking

Colonies

Airport

Factory

Stadium

Foot ball ground

27

LED FLOOD LIGHT







LED Flood Light Back -Chowk with 5050 Power LED & Lens

WATT	COLOUR	I/PVOLTAGERANGE
100	3000K-6500K	AC85-300V@50Hz
200	3000K-6500K	AC85-300V@50Hz
300	3000K-6500K	AC85-300V@50Hz
400	3000K-6500K	AC85-300V@50Hz
500	3000K-6500K	AC85-300V@50Hz
600	3000K-6500K	AC85-300V@50Hz

LED Flood Light Duos

WATT	COLOUR	I/PVOLTAGERANGE
150	3000K/4500k/6500K	AC85-300V@50Hz
200	3000K/4500k/6500K	AC85-300V@50Hz

- Other Colors Also Available As Per requirement.
- Color changing-White/Warm white/Natural white switching operation

Technical Specifications

- Aluminum Die cast body
- Internal Surge protection Up to 6kV
- External Surge protection 10KV as per requirement
- IP66 Drivers (isolated)
- >120-140 Lumens/watt
- Higher volt Auto Cut off
- OSRAM/BRIDGELUX/BMTC Or Equivalent As Per Requirement Operating
- Temperature 10° to 50°
- Average Life 50000 Working Hours

Applications





Pavilion

Party Plot Decorative & Wedding



INDUSTRIAL LIGHT

LED HIGHBAY LIGHT







LED High Bay Light

WATT	COLOUR	I/PVOLTAGERANGE
50	3000K-6500K	AC85-300V@50Hz
80	3000K-6500K	AC85-300V@50Hz
100	3000K-6500K	AC85-300V@50Hz
150	3000K-6500K	AC85-300V@50Hz
200	3000K-6500K	AC85-300V@50Hz
250	3000K-6500K	AC85-300V@50Hz
300	3000K-6500K	AC85-300V@50Hz

LED Well Glass Light

WATT	COLOUR
50	3000K-6500K
80	3000K-6500K

I/PVOLTAGERANGE AC85-300V@50Hz AC85-300V@50Hz

Technical Specifications

- * Aluminum Die cast body
- * Internal Surge protection Up to 6kV
- * * IP66 Drivers(isolated)
- * >120-140 Lumens / watt
- * * Higher volt Auto Cut off
- Operating Temperature-10°to50°
- * * Average Life-50000 Working Hours Warranty 2 years
- * * Bis Approved

Applications





Warehouse

Shed

Factory







UDK Electrical Industries Private Limited

WWW.UDKINDUSTRIES.COM

08455-456614
 +919704317436
 +919505186524











<u>Corporate office :</u> Plot No. 51, ODF Colony-II Venture-I Bypass Road, Royal Junior College, Sangareddy-502001, Telangana, India

Factory Address : 9-170002 vidya Nagar Colony Road No. 3 Sangareddy 502001 , Telangana